STANDARD		PERFORMANCE PLUS PACKAGE
	DIMENSIONS	
178.1"/73.6"/52.9"	Length/Width/Height	178.1"/73.6"/52.9"
100.8"	Wheel base	100.8"
4205 lbs	Weight	4205 lbs
	ENGINE	
5.5-liter AMG-built intercooled supercharged SOHC 24-valve 90° V-8	Engine type	FISKER/KLEEMANN-enhanced 5.5-liter AMG-built intercooled supercharged SOHC 24-valve 90° V-8
High-pressure die-cast alloy cylinder block. Reinforced crankshaft and valvetrain. Alloy heads. Lightweight camshafts. Reinforced engine block, oil pan structure, pistons, connecting rods and crankshaft.	Construction	Adds redesigned pulley wheel, Super Sport camshafts, enlarged stainless steel tubular exhaust headers, down pipes and 70 mm dual exhaust system. KLEEMANN 120 cell metal catalysts.
493 hp @ 6100 rpm	Nominal output/rpm	610 hp @ 5800 rpm
516 lb-ft @ 2750-4000 rpm	Maximum torque	650 lb-ft @ 2200-4700 rpm
Unleaded premium	Fuel grade	Unleaded premium
21.1 gallon/80.0 liters (with 2.6-gallon/ 10.0-liter reserve)	Fuel tank capacity	21.1 gallon/80.0 liters (with 2.6-gallon/ 10.0-liter reserve)
	DRIVETRAIN	
Enhanced 5-speed automatic fingertip manual-style shift buttons	Transmission	Enhanced 5-speed automatic paddle-shift with FISKER-modified aluminum controls for manual style
Rear-wheel drive	Configuration	Rear-wheel drive
	BRAKES	
AMG-enhanced 4-circuit electrohydraulic	Brake system	KLEEMANN High Performance Brakes
14.2" perforated and internally ventilated/AMG 8-piston fixed	Front discs/calipers	Vented and cross-drilled 2-piece discs: 15" (380 x 34 mm), 8-piston forged calipe
13.0" perforated and internally ventilated/AMG 4-piston fixed	Rear discs/calipers	Vented and cross-drilled 2-piece discs: 13" (328 x 28 mm), 4-piston forged calipe
	SUSPENSION	
Independent 4-link	Front suspension	Independent 4-link
Independent 5-arm multilink	Rear suspension	Independent 5-arm multilink
	PERFORMANCE	
4.5 seconds	Acceleration 0-60 mph	3.6 seconds
155 mph (electronically limited)	Top speed	202 mph (electronically limited)
	WHEELS	
Alloy	Material	Alloy
Front: 255/30-20 Rear: 325/25-20	Tire dimensions/type	Front: 255/30-20 Rear: 325/25-20
Collapsible compact limited-use tire on lightweight wheel	Spare tire	Collapsible compact limited-use tire on lightweight wheel