#### 2012 Golf R

## **Technical Specifications**

|                               | Golf R   |   |  |
|-------------------------------|--|---|--|
| ENGINE                        |  |   |  |
|                               | 2 OL inline four ordin   | der 16V   |  |
| Туре                          | <ol><li>2.0L inline four cylin<br/>turbocharged/interc</li></ol>                                   |   |  |
| Bore                          | 3.25 in  | 82.5 mm   |  |
| Stroke                        | 3.65 in  | 92.8 mm   |  |
| Displacement                  | 121 cu in  | 1984 cc   |  |
| Compression Ratio             | 9.8:1  |   |  |
| Horsepower (SAE) @ rpm        | 256 @ 6000   |   |  |
| Maximum torque, lb-ft @ rpm   | 243 @ 2400   |   |  |
| Fuel Requirement              | Premium unleaded   | recommended   |  |
| ENGINE DESIGN                 |  |   |  |
| Arrangement                   | Front mounted, tran  | SVAFEA  |  |
| Cylinder block                | Cast iron  | Sveise  |  |
| Crankshaft                    | Forged steel, five m   | ain hearings  |  |
| Cylinder head                 | Aluminum alloy, cro  |   |  |
| Valvetrain                    |  | amshaft, belt driven, four valves                       |  |
| vaivettain                    |  | nance-free hydraulic lifters,                           |  |
| DRIVETRAIN                    |  |   |  |
| Driven wheels                 | 4Motion permanent  | all-wheel-drive system with Haldex® center differential |  |
| Transmission Gear Ratios:1    | 1st 3.36   |   |  |
|                               | 2nd 2.09   |   |  |
|                               | 3rd 1.47   |   |  |
|                               | 4th 1.09   |   |  |
|                               | 5th 1.10   |   |  |
|                               | 6th 0.91   |   |  |
|                               | Reverse 3.99   |   |  |
|                               | Final I 4.24   |   |  |
|                               | Final II 3.27  |   |  |
| CAPACITIES                    |  |   |  |
| Fuel Tank                     | 14.5 gal   | 55 L  |  |
| STEERING                      |  |   |  |
| Type                          | Rack and pinion: ele   | ectric power assist                                     |  |
| Turns (lock to lock)          | 3.01   | reme perior decide                                      |  |
| Turning Circle (curb to curb) | 35.8 ft  | 10.9 m  |  |
| Ratio                         | 15.6:1   |   |  |
| INTERIOR VOLUME - SAE         |  |   |  |
| EPA Class                     | Compact  |   |  |
| Seating Capacity              | Five   |   |  |
| Passenger Volume              | 93.5 cu ft   |   |  |
| Cargo Volume                  | 15.3 cu ft   |   |  |
|                               | Front  | Rear  |  |
| Volume                        | 51.1 cu ft   | 42.4 cu ft  |  |
| Headroom (in/mm)              | 39.3/998   | 38.5/979  |  |
| Shoulder room (in/mm)         | 54.7/1390  | 53.6/1362   |  |
| Legroom (in/mm)               | 41.2/1046  | 35.5/901  |  |
| BODY, CHASSIS AND SUSPENSION  |  |   |  |
| Type                          | Unitary construction   |   |  |
| Body Material                 | Steel stampings  |   |  |
| Front Suspension              | Strut-type with lower control arms, coil springs, telescopic dampers, anti-roll bar                |   |  |
| Rear Suspension               | Multilink with coil sp   | rings, telescopic dampers, anti-                        |  |
|                               | roll bar   |   |  |
| Brakes                        | Power assisted, dual circuit, 13.6 x 1.2-in vented front discs and 12.2 x 0.9-in vented rear discs |   |  |
| Anti-Lock Braking System      |  | neels, three-channel                                    |  |
|                               | with electronic brake  |   |  |
|                               | distribution   |   |  |
| Stability Control             | Standard Electronic  | Stability Control                                       |  |
| <b>y</b> · ·                  | (ESC)  | •   |  |
| Parking Brake                 | Mechanical   |   |  |
| Wheels/Tires                  | 18-in x 7.5J aluminu   | im-alloy wheels   |  |
|                               | 225/40 R18 92H all-  |   |  |
|                               |  |   |  |

## 2012 Golf R

# **Technical Specifications**

#### Golf R

| DIMENSIONS               |                 |
|--------------------------|-----------------|
| Wheelbase (in/mm)        | 101.5/2578      |
| Front Track (in/mm)      | 60.4/1533       |
| Rear Track (in/mm)       | 59.6/1514       |
| Length (in/mm)           | 165.8/4212      |
| Width (in/mm)            | 70.3/1786       |
| Height (in/mm)           | 57.5/1469       |
| Ground Clearance (in/mm) | 5.0/128         |
| WEIGHTS                  |                 |
| Curb Weight              | 3325 lb 1508 kg |
| GVWR                     | 4542 lb 2060 kg |
| Payload                  | 1118 lb 507 kg  |
| FUEL CONSUMPTION         | Manual          |
| City mpg                 | 19              |
| Highway mpg              | 27              |

Specifications, equipment, options, and prices are subject to change without notice.





